



Johnsonite®

I.D. Inspiration™



 **Tarkett**



On the cover- 24205009 Wenge | Black B | 24207120 Oxide | Black Steel CG



24201003 Antik Oak | Dark Grey WG | 24201024 English Oak | Beige CB | 24201109 Contemporary Oak | Grey CB











## TECHNICAL DATA

## STANDARDS

Type of Floor Covering		Solid Vinyl Tile
Classification	ASTM F1700	Class III Type B
Wear Layer Thickness		ID70: .028" (0.7 mm)   ID55: .022" (0.55 mm)
Polyurethane Reinforced		Yes
Total Thickness	ASTM F386	.098" (2.5 mm)
Static Load Limit	ASTM F970	Passes
Electrostatic Propensity	EN1815	≤ 2kV
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0
Resistance to Light	ASTM F1515	ΔE ≤ 8.0
Slip Resistance	ASTM D2047	SCOF ≥ 0.6
Flame Resistance	ASTM E648	Class 1
Chemical Resistance	ASTM F925	Good

Colors: 24 Woods

ID70: 24201   ID55: 24231			
Size: 7.87" x 48" (20cm x 122cm)	Quantity: 15 pieces per ctn	Square Feet: 39.35 ft <sup>2</sup> (3.66 m <sup>2</sup> )	Weight: 35 lbs. per ctn (15.87 kg)
ID70: 24205   ID55: 24235			
Size: 6.56" x 39.37" (16.66cm x 100cm)	Quantity: 22 pieces per ctn	Square Feet: 39.35 ft <sup>2</sup> (3.66 m <sup>2</sup> )	Weight: 35 lbs. per ctn (15.87 kg)

Colors: 6 Tiles (Stone, Abstract, Textile)

ID70: 24207   ID55: 24237			
Size: 19.68" x 19.68" (50cm x 50cm)	Quantity: 15 pieces per ctn	Square Feet: 40.34 ft <sup>2</sup> (3.75 m <sup>2</sup> )	Weight: 35 lbs. per ctn (15.87 kg)

Please visit [tarkettna.com](http://tarkettna.com) for the most updated installation, cleaning and maintenance instructions.