

# LUXURY VINYL PLANK

## I.D. Inspiration™ 70

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Luxury vinyl floor covering with PUR-reinforced surface plank style. Suitable for commercial working environments and offices:

- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias, lavatories
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Exam rooms, lobbies, corridors
- Hospitality – Corridors, vending areas, lobbies

### 1.2. Manufacturer:

Tarkett Phone: (800) 899-8916  
30000 Aurora Rd. (440) 543-8916  
Solon, Ohio 44139 Tech: Ext 9297  
Web: www.tarkettna.com Samples: Ext 9299  
E-mail: info@johnsonite.com

### 1.3. Proprietary Product Description:

1.3.1. Construction: Tarkett I.D. Inspiration is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 28 mil PVC wear layer.

### 1.3.2. Styles:

- I.D. Inspiration 70
- Reinforced Polyurethane Surface Treatment
- Wear layer Thickness: 28 mil (0.71 mm)
- Overall thickness .100" (2.5mm)
- Sizes:
  - Planks: 6.56" x 39.37" (16.7cm x 100cm)
  - Wide Planks: 7.87" x 48" (19.76cm x 121.91cm)
  - Tiles: 19.68" x 19.68" (50cm x 50cm)

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Tile material – Meets ASTM F 1700, Class III, Type B performance
- 2.2. Residual Indentation (ASTM F1914): Passes
- 2.3. Static coefficient of friction (ASTM D 2047): Minimum 0.5 SCOF
- 2.4. Static Load Limit (ASTM F 970): Passes with 250 psi with less than 0.005" residual indentation
- 2.5. Dimensional Stability (ASTM F 2199): Passes
- 2.6. Resistance to Heat (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.7. Resistance to Light: (ASTM F 1515):  $\Delta\Sigma \leq 8.0$
- 2.8. Chemical Resistance (ASTM F 925): Passes

2.9. Fire Performance, Critical Radiant Flux (ASTM E648): Minimum of 0.45 W/cm<sup>2</sup> - Class 1

### 3. INSTALLATION

See I.D. Inspiration Luxury Vinyl Plank installation instructions for complete details.

#### 3.1 Adhesives:

- Tarkett 926 Adhesive:  
Approximate Coverage:  
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 959 Adhesive:  
Coverage:  
Porous Substrate: 150-175 sq. ft. per gallon  
Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive:  
Approximate Coverage:  
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett RollSmart Adhesive:  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 20 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to I.D. Inspiration maintenance instructions for complete details.

### 7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916



THE ULTIMATE  
FLOORING EXPERIENCE

Technical Services Department  
30000 Aurora Road, Solon, Ohio 44139  
(800) 899-8916 ext 9297  
Fax (440) 632-5643  
email: info@johnsonite.com  
[www.tarkettna.com](http://www.tarkettna.com)