



JOHNSONITE RESILIENT WALL BASE

Masquerade Wall Base

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Masquerade Resilient Wall Base profiles replicate the look of wood and stone.

1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarkettna.com	Samples: Ext 9299
E-mail: info@johnsonite.com	

1.3. Proprietary Product Description:

1.3.1. Construction: Johnsonite Masquerade Resilient Wall Base is manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861 Standard Specification for Resilient Wall Base, Type TP, and Group 1.

1.3.2. Styles & Physical Characteristics:

Viewpoint™ (MW-XX-V): 3/8" (9.5 mm) thick by 4" (10.2 cm) height with a 45° angular top, 5 per carton, 8 ft lengths, 40 ft (12.2 m) per carton, 46 lbs (20.9 kg) per carton

Classic™ (MW-XX-Z): 3/8" (9.5 mm) thick by 5-1/4" (13.3 cm) height, 6 per carton, 8 ft lengths, 48 ft (14.6m) per carton, 54 lbs (kg) per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.

2.2. Chemical resistance (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution

2.3. Resistance to light (ASTM F 1515): ΔE < 8

2.4. Fire Resistance:

ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I

3. INSTALLATION

3.1. See Johnsonite Masquerade wall base installation instructions for complete details.

3.2. Adhesives:

Tarkett 960 Cove Base Adhesive (Porous surfaces):

Application: 1/8" x 1/8" x 1/8" square notched trowel

Approximate coverage:

Viewpoint: 200 to 250 linear feet/gallon

Classic: 145 to 195 linear feet/gallon

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

1 kg Unit (0.95 Qt.) – 24 to 36 sq. ft.

6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite Masquerade Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



Technical Services Department

30000 Aurora Road, Solon, Ohio 44139

(800) 899-8916 ext 9297

Fax (440) 632-5643

email: info@johnsonite.com

www.tarkettna.com