

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Vent Cove Wall Base

1.2. Manufacturer:

Tarkett
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@johnsonite.com

Phone: (800) 899-8916
(440) 543-8916
Tech: Ext 9297
Samples: Ext 9299

1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite Vent Cove Wall Base is manufactured from a homogeneous composition of 100% synthetic rubber, high quality additives, and colorants designed specifically to meet the performance requirements of ASTM F-1861, Type TS, Group 1 (solid) Standard Specification for Resilient Wall Base. Vent Cove Wall Base is designed for hardwood floating floor constructions and is equipped with vertical, semi-circular vents along the back side of the wall base to ensure proper air circulation under the floor and permits free expansion of the floor. Outside corners with 3 - 11/16" (9.37 cm) returns are available.

1.3.2. Styles:

- Specify Wall Base M-900 for Black or M-901 for Brown
- Size: 4" (10.16 cm) high by 5/16" (7.94 mm) thick covered profile with a 3" (7.62 cm) long by 3/8" (9.53 mm) thick toe. Back surface grooved with vertical semi-circular (5/32" radius) vents (15 vents per 4 ft. length).
- Length: 4' (1.22 m) Packaging: 16 lengths per carton
- Outside corners available: CO-910 for color Black or CO-911 for Brown with 3 - 11/16" (9.37 cm) returns.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness:** ASTM D 2240 – Not less than 85 Shore A
- 2.2. **Fire Resistance:** Meets ASTM E 648 – Class I
- 2.3. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods as described in ASTM F-1861.

3. INSTALLATION

See vent cove wall base installation instructions for complete details.

3.1. Adhesives:

- **Tarkett 960 Adhesive:**
Coverage:
Porous Substrate: 200-250 linear ft. per gallon
- **Tarkett 946 Premium Contact Adhesive:**
Coverage:
Non-porous Substrate: 24 to 36 sq. ft. per 1 kilogram unit
144 to 215 sq. ft. per 6 kilogram unit

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Vent Cove Installation and Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.