



HETEROGENEOUS SHEET FLOORING

Acczent Wood Acoustiflor

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Heterogeneous sheet vinyl flooring with a foam underlayer designed to reduce noise transmission and absorbs impacts.

1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarkettna.com	Samples: Ext 9299
E-mail: info@johnsonite.com	

1.2.1. Proprietary Product Description:

1.2.2. Construction: Johnsonite's Acczent Wood Acoustiflor wear layer is composed of 90% binder content, with a polyurethane reinforced (PUR) construction to minimize maintenance. Underlayer foam provides added comfort under foot and reduces noise transmission.

1.2.3. Styles:

- ACWAC-R
- Overall thickness of 0.136" nominal (3.45 mm) total thickness
- Packaging: Available in 6' 6" (2 m) wide and approximately 75' 9" linear feet (23 m) per roll

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Sheet material meets requirements of ASTM F 1303, Type I, Grade 1
- Heat Stability by color change (ASTM F 1514): $\Delta E \leq 8.0$
- Light Stability by color change (ASTM F 1515): $\Delta E \leq 8.0$
- Electrostatic Propensity (EN 1815): $< 2 \text{ kV}$
- Static coefficient of friction (ASTM D 2047): > 0.6
- Static Load Limit (ASTM F 970): Passes 250 psi load requirement
- Impact Sound Transmission (ASTM E 492): 61 IIC
- Fire Resistance:
 - ASTM E 648/NFPA 253 (Critical Radiant Flux) – Class 1

3. INSTALLATION

See Acczent heterogeneous sheet flooring installation instructions for complete details.

3.1. Roll Adhesive:

- Tarkett 925 Adhesive Coverage:
 - Porous Substrate: 250-300 sq. ft./gal.
 - Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
 - Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett RollSmart Adhesive Coverage:
 - 350 - 400 sq. ft. per gallon (3/8" Nap Paint Roller used with a paint tray)
- Tarkett 901 SpraySmart Adhesive Coverage:
 - 150 sq. ft. per. container

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Homogeneous sheet maintenance instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
 30000 Aurora Road, Solon, Ohio 44139
 (800) 899-8916 ext 9297
 Fax (440) 632-5643
 email: info@johnsonite.com
www.tarkettna.com