

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Edge Guard Mouldings

1.2. Manufacturer:

Tarkett Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139 Tech: Ext 9297
Web: www.tarkettna.com Samples: Ext 9299
E-mail: info@johnsonite.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite Resilient Chair Rail Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Johnsonite Chair Rail Mouldings are designed for interior applications only.

1.3.2. Physical Characteristics:

Fortis



CHR-XX: 3" (7.62cm) wide by 3/16" (4.75mm) thick profile

- Lengths: 8 ft. (2.4m)
- Packaging: 10 per carton [80 ft (24.4m) per carton]
- Weight 3.2 lbs (1.45kg) per piece [32 lbs (14.5kg) per carton]

Bastion



CHR-XX-B: 4" (10.16cm) wide by 5/16" (7.94mm) thick profile

- Lengths: 8 ft. (2.4m)
- Packaging: 6 per carton [48 ft. (14.6m) per carton]
- Weight: 4.5 lbs (2.04kg) per piece [27 lbs (12.2kg) per carton]

Rampart



CHR-XX-C: 4" (10.16cm) wide by 3/8" (9.53mm) thick profile

- Lengths: 8 ft. (2.4m)
- Packaging: 5 per carton [40 ft (12.2m) per carton]
- Weight: 6 lbs (2.72kg) per piece [36 lbs (16.3kg) per carton]

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Hardness:** ASTM D 2240 - Not less than 85 Shore A

2.2. **Fire Resistance:** ASTM E 84/NFPA 255 (Steiner Tunnel Test):
Class B

3. INSTALLATION

3.1. See Johnsonite Resilient Chair Rail Moulding installation and maintenance instructions for complete details.

3.2. Adhesives:

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush on T-Moulding and track on mitered corner areas

Approximate coverage:

1 kg Unit (0.95 Qt) – 24 to 36 sq. ft.

6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite Resilient Chair Rail Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.