



HOMOGENEOUS SHEET/TILE FLOORING

Contract Plus

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Homogeneous sheet and tile floor coverings, non-directional patterned, designed for durability and commercial interiors. Recommended areas for use:

- Education – Classrooms, corridors, multipurpose rooms, gymnasiums, laboratories, cafeterias
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories
- Hospitality – Corridors, vending areas, lobbies, bathrooms

1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarkettna.com	Samples: Ext 9299
E-mail: info@johnsonite.com	

1.3. Proprietary Product Description:

Construction: Contract Plus is composed of a tough, UV-cured factory applied polyurethane finish (PU) on a homogenous vinyl construction.

1.3.1. Styles:

- CON-R (Rolls) or CON-JT (Tiles)
- Overall thickness: 0.080" (2.0 mm)
- Available in 6' 6" (2 m) wide rolls and 24" by 24" (60.9 cm x 60.9 cm) tiles.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Rolls - Meets the following performance standards of ASTM F 1913 for homogeneous single layered vinyl floor covering.
- 2.2. Tiles - Meets following performance standards of ASTM F 1700, Class I, Type A
- 2.3. Heat Stability by Color Change (ASTM F 1514): $\Delta E \leq 8$
- 2.4. Flexibility (ASTM F 137): Passes with 1-1/2" mandrel
- 2.5. Chemical Resistance (ASTM F925): Passes
- 2.6. Static coefficient of friction (ASTM D 2047): ≥ 0.5
- 2.7. Static Load Limit (ASTM F 970): Passes 250 PSI with less than 0.005 in. residual indentation
- 2.8. Fire Performance (ASTM E 648 Flooring Radiant Panel): Class 1

3. INSTALLATION

See homogeneous sheet or tile flooring installation instructions for complete details.

3.1. Roll Adhesives:

- Tarkett 925 Adhesive Coverage:
Porous Substrate: 250-300 sq. ft./gal.
Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- Tarkett RollSmart Adhesive Coverage:
350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)
- Tarkett 901 SpraySmart Adhesive Coverage:
150 sq. ft. per. Container
- Tarkett Cold Weld Liquid Coverage: 175 – 200 lin. ft. per. 4.5 oz. tube

3.2. Tile Adhesives:

- Tarkett 926 Adhesive Coverage:
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive Coverage:
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Contract Plus Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
 30000 Aurora Road, Solon, Ohio 44139
 (800) 899-8916 ext 9297
 Fax (440) 632-5643
 email: info@johnsonite.com
www.tarkettna.com