

LUXURY VINYL PLANK

I.D. Inspiration™

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Luxury vinyl floor covering with PUR-reinforced surface plank style. Suitable for commercial working environments and offices:

- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias, lavatories
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Healthcare – Exam rooms, lobbies, corridors
- Hospitality – Corridors, vending areas, lobbies

1.2. Manufacturer:

Tarkett	Phone:	(800) 899-8916
30000 Aurora Rd.		(440) 543-8916
Solon, Ohio 44139	Tech:	Ext 9297
Web: www.tarkettna.com	Samples:	Ext 9299
E-mail: info@johnsonite.com		

1.3. Proprietary Product Description:

1.3.1. Construction: Johnsonite I.D. Inspiration is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 28 mil PVC wear layer.

1.3.2. Styles:

- I.D. Inspiration (INS-P)
- Reinforced Polyurethane Surface Treatment
- Wear layer Thickness: .028" (0.7mm)
- Overall thickness .100" (2.5mm)
- Planks Size: 6.56" x 39.37" (16.7cm x 100cm)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B, performance standards for solid vinyl floor tile
- 2.2. Static coefficient of friction: (ASTM D 2047): ≥ 0.5 SCOF
- 2.3. Static Load Limit (ASTM F 970): Passes with 250 psi with less than 0.005" residual indentation
- 2.4. Resistance to Heat (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.5. Resistance to Light (ASTM F 1515): $\Delta\Sigma \leq 8.0$
- 2.6. Chemical Resistance (ASTM F 925): Passes
- 2.7. Fire Performance - Critical Radiant Flux (ASTM E 648): ≥ 0.45 W/cm² - Class 1

3. INSTALLATION

See I.D. Inspiration Luxury Vinyl Plank installation instructions for complete details.

3.1. Adhesives:

- Tarkett 926 Adhesive:
Approximate Coverage:
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 959 Adhesive:
Coverage:
Porous Substrate: 150-175 sq. ft. per gallon
Non-porous Substrate: 250-300 sq. ft. per gallon
- Tarkett 975 Two-Part Polyurethane Adhesive:
Approximate Coverage:
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to I.D. Inspiration maintenance instructions for complete details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916 ext 9297
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com