



# JOHNSONITE RESILIENT MOULDINGS

## Quarter Round Mouldings

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

#### 1.1. Proprietary Product: Resilient Quarter Round Mouldings

#### 1.2. Manufacturer:

Tarkett  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkettna.com](http://www.tarkettna.com)  
E-mail: [info@johnsonite.com](mailto:info@johnsonite.com)

Phone: (800) 899-8916  
(440) 543-8916  
Tech: Ext 9297  
Samples: Ext 9299

#### 1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite Resilient Quarter Round Mouldings are manufactured from a proprietary thermoplastic rubber compound, high quality additives, and colorants. Johnsonite Quarter Round Mouldings are designed for interior applications only.

#### 1.3.2. Styles:

**QTR-XX-A:** 1/2" (12.7 mm) wide by 1/2" (12.7 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 20 lengths [160 ft. (48.8 m)] per carton; weight of carton is 24 lbs (10.9 kg).

**QTR-XX-D:** 3/4" (19.05 mm) wide by 3/4" (19.05 mm) high radius profile with a pressure sensitive adhesive backing, length is 8 ft. (2.49 m), 10 lengths [140 ft. (42.67 m)] per carton, weight of carton is 30 lbs (13.6 kg).

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

### 3. INSTALLATION

3.1. See Johnsonite Resilient Moulding installation and maintenance instructions for complete details.

3.2. **Adhesive:** Self-stick tape applied to Quarter Round Mouldings

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

