



JOHNSONITE RESILIENT WALL BASE

rePLACE Wall Base

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: rePLACE Resilient Wall Base System

1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarketta.com	Samples: Ext 9299
E-mail: info@johnsonite.com	

1.3. Proprietary Product Description:

1.3.1. Construction: The Johnsonite rePLACE Resilient Wall Base System is manufactured from a thermoplastic rubber formulation designed specifically to meet the dimensional and performance requirements of ASTM F-1861, Type TP, Group 1 (solid) Standard Specification for Resilient Wall Base.

1.3.2. Physical Characteristics:

rePLACE WALL BASE AND TRACK

- Prominent™ (RB-XX-A): 7/16" (11.1 mm) track and base thickness, 4-3/8" (11.11 cm) high wall base profile, x 4 ft long wall base profile with integral locking tabs on the back of the profile which interlock onto wall track (RBT-00).
- Tempo™ (RB-XX-F): 7/16" (11.1 mm) track and base thickness, 4-3/8" (11.11 cm) high x 4 ft long wall base profile with integral locking tabs on the back of the profile which interlock onto wall track (RBT-00).
- Gepetto™ (RB-XX-G): 7/16" (11.1 mm) track and base thickness, 4-1/2" (11.45 cm) high wall base profile with integral locking tabs on the back of the profile which interlock onto wall track (RBT-00).
- rePLACE Track (RBT-00): rePLACE Wall Track is required for the installation of the RB-xx-A, RB-xx-F and RB-xx-G Wall Base profiles and shall be mechanically fastened to the wall using screws appropriate for the type of substrate material.

Packaging (Profiles and Track): 4 feet lengths, 20 pieces per carton [80 linear ft (24.4 m)]

rePLACE CORNERS AND END STOPS (for use with all profiles)

- Inside Corner (RBIC-XX): 4-5/8" (11.75 cm) high, 25 pieces per carton
- Outside Corner (RBOC-XX): 4-5/8" (11.75 cm) high, 25 pieces per carton
- Right End Stop (RBRS-XX): 4-5/8" (11.75 cm) high, 25 pieces per carton
- Left End Stop (RBLs): 4-5/8" (11.75 cm) high, 25 pieces per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.
- 2.2. Flexibility: Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.
- 2.3. Chemical resistance (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution
- 2.4. Resistance to light (ASTM F 1515): $\Delta E < 8$
- 2.5. Fire Resistance:
 - ASTM E 84/NFPA 255 (Flame/Smoke) – Class A, < 450
 - ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I

3. INSTALLATION

- 3.1. See Johnsonite rePLACE wall base installation instructions for complete details.
- 3.2. Adhesives: Not required

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite rePLACE Resilient Wall Base Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarketta.com or contact Tarkett at 1-800-899-8916.

Technical Services Department
 30000 Aurora Road, Solon, Ohio 44139
 (800) 899-8916 ext 9297
 Fax (440) 632-5643
 email: info@johnsonite.com
www.tarketta.com