

ENTRANCE BARRIER MATTING

Terra-Turf Entrance Matting

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Terra-Turf Rubber Floor Tile

1.2. **Manufacturer:**

Tarkett
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@johnsonite.com

Phone: (800) 899-8916
(440) 543-8916
Tech: Ext 9297
Samples: Ext 9299

1.3. **Proprietary Product Description:**

1.1.1. **Construction:** Johnsonite Terra-Turf Rubber Floor Tiles are manufactured of recycled aircraft and truck tire strips adhered with hot-melt adhesive to a reinforced nylon scrim backing. This rugged, yet handsome, carpet-like tile is highly resistant and spike-proof. Its non-skid surface is ideal for ramps, concourses, golf pro shops, entrances, skating rinks, schools, and other sports arenas. Johnsonite Terra-Turf Rubber Floor Tiles are designed for interior or exterior applications, but not recommended for commercial kitchen environments.

1.3.1. **Physical Characteristics:**

- **Color:** Black/brown
- **Size/Packaging:**
 - 12" x 12" x 3/8" thickness (30.48 cm x 30.48 cm - 9.53 mm thickness)
 - 12" x 25 ft. coils x 3/8" thickness (30.48 cm x 7.62 m - 9.53 mm thickness)
 - 25 tiles or 1 coil per carton.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 2.2. **Abrasion Resistance** (ASTM D 3389): <1.0 gm weight loss
- 2.3. **Slip Resistance** (ASTM D 2047): Exceeds static coefficient of friction of 0.5
- 2.4. **Fire Resistance** (ASTM D2859): Passes

3. INSTALLATION

See Terra-Turf installation instructions for complete details.

3.1. **Adhesives:**

- **Tarkett Terra-Turf Adhesive Coverage:**
 - Porous Substrate: 125-150 sq. ft. per gallon
 - Non-porous Substrate: 150-175 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Terra-Turf maintenance instructions for complete details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916 ext 9297
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com