



# JOHNSONITE RESILIENT MOULDINGS

## T-Mouldings & Track Bases

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

#### 1.1. Proprietary Product: Resilient Mouldings

#### 1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: <a href="http://www.tarkettna.com">www.tarkettna.com</a>	Samples: Ext 9299
E-mail: <a href="mailto:info@johnsonite.com">info@johnsonite.com</a>	

#### 1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite resilient T-Moulding Transitions are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Johnsonite transitions are designed for interior applications only.

#### 1.3.2. Styles:

##### T- Mouldings:

**CE-XX-A:** 1/4" (6.35mm) and 5/16" (7.94mm) sponge back carpet to 1/8" (3.18mm) resilient, 1-1/16" (2.70cm) cap with 1/4" (6.35mm) long snap-in stem

**CE-XX-C:** 1/2" (12.7mm) ceramic to 3/8" (9.53mm) or 1/4" (6.35mm) carpet, 1-5/16" (3.33cm) cap with 1/2" (12.7mm) long snap-in stem

**CD-XX:** 1-1/2" (3.81cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

**CD-XX-A:** 1-1/2" (3.81cm) wide level transition for adjoining 1/2" (12.7mm) materials. 1/2" (12.7mm) long snap-in stem

**CD-XX-B:** 1/2" (12.7mm) materials to 1/8" (3.18mm) resilient, 1-1/2" (3.81cm) cap with 1/2" (12.7mm) snap-in stem

**CD-XX-C:** 3/4" (1.91cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

**CD-XX-W:** 3" (7.62cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

##### Track Bases:

**CDB 00-A:** Single Flange Vinyl Track Base for glue down carpet installations.

**MT-00-A:** Single Flange Aluminum Track Base for glue down carpet installations.

**MT-00-B:** Single Flange Aluminum Track Base for stretch-in carpet installations.

**MTC-00-A:** Single Flange Aluminum Contour-able Track Base for glue down carpet installations, 6 ft. minimum bend radius

**MTC-00-B:** Single Flange Aluminum Contour-able Track Base for stretch-in carpet installations, 6 ft. minimum bend radius

#### 1.3.3. Physical Characteristics:

T-Moulding & Track Base Lengths: 12 ft (3.66m)

##### Packaging:

CDB-00-A - 20 lengths [240 ft. (73.15 m)] per carton

CD-XX-W – 10 pc/carton

All other T-Moulding profiles – 20 lengths per carton

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

### 3. INSTALLATION

3.1. See Johnsonite Resilient Moulding installation and maintenance instructions for complete details.

#### 3.2. Adhesives:

**Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush on T-moulding and track on mitered corner areas

Approximate coverage:

1 kg Unit (0.95 Qt) – 24 to 36 sq. ft.

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Johnsonite Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

#### Technical Services Department

30000 Aurora Road, Solon, Ohio 44139

(800) 899-8916 ext 9297

Fax (440) 632-5643

email: [info@johnsonite.com](mailto:info@johnsonite.com)

[www.tarkettna.com](http://www.tarkettna.com)