

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Homogeneous Veneto Acoustiflor floorcovering, single layer on jute backing with 1.3 mm polyurethane foam underlayer.

1.2. Manufacturer:

Tarkett
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@johnsonite.com

Phone: (800) 899-8916
(440) 543-8916
Tech: Ext 9297
Samples: Ext 9299

1.3. Proprietary Product Description:

1.3.1. Construction: Veneto Acoustiflor floorcovering consists of a homogeneous layer composed of oxidized linseed oil, natural resins, wood and cork flour, limestone, and pigments affixed to jute backing with a polyurethane foam underlayer. The surface has a proprietary xf²™ treatment for reduced maintenance.

1.3.2. Styles:

- VENAC-R
- Total Thickness: 0.150" (3.8 mm)
- Packaging: 6' 6" (2 m) wide and approximate length of 88' 7" (27 m) per roll

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Meets ASTM F 2034 – Performance standards for sheet linoleum floor covering
- Static Load Limit (ASTM F 970): Passes with a 175 psi load requirement and results of less than 0.005 inch residual indentation
- Impact Sound Transmission (ASTM E492): 59 IIC
- Sound Impact Reduction: (ASTM E 492): 8 dB
- Heat Stability by Color Change (ASTM F1514): $\Delta E \leq 8.0$
- Light Stability by Color Change: (ASTM F1515): $\Delta E \leq 8.0$
- Static coefficient of friction (ASTM D 2047): > 0.6
- Chemical Resistance (ASTM F 925): Passes
- Fire Resistance:
 - ASTM E 648/NFPA 253 (Critical Radiant Flux), Class 1
 - ASTM E 662/NFPA 258 (Smoke Density), less than 450

3. INSTALLATION

3.1. See Harmonium xf² Veneto Acoustiflor sheet installation instructions for complete details.

3.2. Adhesives:

- Tarkett 950 Adhesive:
Coverage:
Porous Substrate: 100-125 sq. ft./gal.
Non-porous Substrate: 125-150 sq. ft./gal.
- Tarkett 975 Two-Part Polyurethane Adhesive:
Approximate Coverage:
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Harmonium xf² Veneto Acoustiflor sheet maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.