

Product Specification

SpraySmart 901 Spray Adhesive

1. PROPRIETARY PRODUCT

1.1. **Product Description:** Tarkett SpraySmart™ 901 is a solvent-free spray adhesive formulated for the installation of many Tarkett Resilient Floorings.

1.2. **Manufactured For:**

Tarkett USA Inc. Phone: (800) 899-8916
30000 Aurora Rd. Tech: Ext 9297
Solon, Ohio 44139
Web: www.tarkettna.com
E-mail: info@tarkett.com Fax: (440) 632-8920

1.3. **Physical Characteristics:**

- Base –Acrylic
- Color – Light blue
- Shelf Life –2 year in unused, properly stored container
- Freeze thaw- Protect from freezing
- Working Time – 2 hours
- Drying Time – Dry to the touch
- Contains no hazardous or carcinogenic ingredients as defined by OSHA chemicals and meets all federal, state and local air quality regulations.
- SCAQMD Rule1168 – VOC compliant (0 g/l calculated)

1.4. **Adhesive Coverage:**

VCT

Coverage: 200 sq. ft. per 22 ounce can

VET - SVT

Coverage: 160 sq. ft. per 22 ounce can

Vinyl Sheet

Coverage: 150 sq. ft. per 22 ounce can

Rubber Tile

Coverage: 80 sq. ft. per 22 ounce can

2. SUBSTRATE PREPARATION

SpraySmart™ 901 can be used in occupied buildings that require rapid project turn-a-round and immediate post-installation access while greatly reducing the handling and application requirements associated with conventional adhesives.

SpraySmart™ 901 may be used on porous or non-porous surfaces such as metal, wood, terrazzo, and on or above grade concrete substrates with up to 90% RH as determined per latest version of ASTM F2170 or 8lbs in 24hrs per 1000 ft² per latest version of ASTM F1869 and pH between 7.0 - 10.0. **NOTE:** Installation of rubber flooring is limited to 85% RH or 7lbs MVER and 7.0-10.0 pH.

The interior air temperature and Relative Humidity must be maintained between 65 - 85°F and 40-60% RH, and the substrate temperature should be at least 5 degrees F. higher than the Dew Point. Testing the substrate with an impedance is recommended due to possible issues related to topical moisture from dew point conditions.

3. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

4. Traffic:

- Normal traffic on flooring installations may resume as soon as the installation is completed.
- For recommended sheet products, seams can be heat welded once the flooring has been rolled twice in both directions with a 100 lb, three-section roller.
- Wait at least 48 hours before beginning initial maintenance.

5. LIMITED WARRANTY

Adhesive warranty is a “system warranty” covered under the product that is recommended to be installed in conjunction with this adhesive. Refer to Tarkett limited warranty.

6. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, Safety Data Sheet and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at (800) 899-8916.