

### Track Base Mouldings

#### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 Proprietary Product: Resilient Vinyl and Aluminum Track Base Mouldings (These track bases receive CE and CD mouldings)

1.2 Manufacturer:

Johnsonite, Inc.,  
16910 Munn Road  
Chagrin Falls, Ohio 44023  
Phone: (800) 899-8916  
(440) 543-8916  
Fax: (440) 543-8920  
Tech: Ext 297  
Samples: Ext 299  
Web: [www.johnsonite.com](http://www.johnsonite.com)  
E-mail: [info@johnsonite.com](mailto:info@johnsonite.com)

1.3 Proprietary Product Description

1.3.1 **Construction:** Johnsonite Track Base Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC) or aluminum. All Track Bases and companion CE and CD transitional mouldings comply with A.D.A. requirements of Section 4.5.2 Changes of Level. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Track Base Mouldings are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2 Styles

**CDB 00-A:** Single Flange Vinyl Track Base for glue down carpet installations.

**MT-00-A:** Single Flange Aluminum Track Base for glue down carpet installations.

**MT-00-B:** Single Flange Aluminum Track Base for stretch-in carpet installations.

**MTC-00-A:** Single Flange Aluminum Contour-able Track Base for glue down carpet installations, 6 ft. minimum bend radius

**MTC-00-B:** Single Flange Aluminum Contour-able Track Base for stretch-in carpet installations, 6 ft. minimum bend radius

1.3.3 **Physical Characteristics**

Length: 12 ft. (3.66 m)

Packaging: CDB-00-A - 20 lengths [240 ft. (73.15 m)] per carton

All MT bases - 12 lengths [144 ft. (43.9 m)] per carton.

#### 2. INSTALLATION

2.1 The installation of Johnsonite Track Base Mouldings should not begin until the work of all other trades has been completed, especially overhead trades. Areas to receive track base mouldings shall be clean, fully enclosed, weathertight, and maintained at a uniform temperature of at least 65°F for 24 hours before, during, and after the installation is completed. The track base mouldings and adhesives shall be conditioned in the same manner. The floor

surface shall be smooth, flat, permanently dry, clean and free of all foreign material, such as dust, paint, grease, oils, solvents, curing and hardening compounds, sealers, asphalt, and old adhesive residue. Do not install on exterior surfaces subject to weather. Track Base Mouldings shall be securely adhered to the floor utilizing the manufacturer's recommended adhesive or by mechanical means. Many of the track base mouldings may be formed in a radius.

Johnsonite recommends a radius of not less than 6 feet or greater pending on the cross-sectional profile of the companion snap-in moulding. An actual test should be performed with the moulding to ensure conformance to the application. Track Base Mouldings shall be rolled, with a J-hand roller, after installation, to ensure proper bonding when installed with adhesive.

2.1.1 **Adhesives:**

Porous and Nonporous Substrates

Johnsonite #945 Contact Bond Adhesive

Application: Brush or roller

Coverage: Approximately 360 sq. ft./gallon

**Installation Manual:** Refer to Johnsonite Resilient Mouldings Installation Instructions for complete installation details.

#### 3. AVAILABILITY AND COST

3.1 Available through authorized Johnsonite distributors nationwide.

#### 4. WARRANTY

4.1 Limited 1 year warranty. For complete details, contact Johnsonite or an authorized Johnsonite distributor.

#### 5. AVAILABILITY AND COST

5.1 Available through authorized Johnsonite distributors nationwide.

#### 6. MAINTENANCE

6.1 Refer to Johnsonite Carpet Threshold Mouldings Installation Instructions for complete maintenance details.

#### 7. TECHNICAL SERVICES

7.1 Samples: Submittal samples for verification and approval available upon request from Johnsonite. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7.2 For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.johnsonite.com](http://www.johnsonite.com) or contact Johnsonite at 1-800-899-8916.