



LUXURY FLOOR

Aloft™ Click

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1.1. **Proprietary Product:** Luxury vinyl plank click floor covering with a 12 mil wear layer protection system.

1.2. **Manufacturer:**

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: www.tarkettna.com	Samples: Ext 9299
E-mail: info@johnsonite.com	

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Aloft Click Luxury Vinyl Flooring is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 12 mil wear layer protection system.

1.3.2. **Packing/Size:**

- **Wearlayer Thickness:** 0.012" (0.3 mm)
- **Overall thickness:** .125" (3.2 mm)
- **Plank size:** 5.906" x 48.031" (15.0cm x 122cm)
- **Packaging:** 14 planks/carton, 27.58 sq. ft. (2.56 m²)
- **Weight:** 34.17 lbs. (15.50 kg) / carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Size, Tolerance, Squareness (ASTM F 2055):** Passes
- 2.2. **Resistance to Heat (ASTM F1514):** $\Delta \Sigma \leq 8.0$
- 2.3. **Resistance to Light (ASTM F 1515):** $\Delta \Sigma \leq 8.0$
- 2.4. **Flexibility (ASTM F 137):** Passes 1" mandrel
- 2.5. **Short Term Indentation (ASTM F 1914):** Passes
- 2.6. **Chemical Resistance (ASTM F 925):** Passes
- 2.7. **Static Load Limit (ASTM F 970):** Passes with 250 PSI with less than 0.005" residual indentation
- 2.8. **Static coefficient of friction (ASTM D 2047)** minimum 0.5 SCOF
- 2.9. **Fire Performance, Critical Radiant Flux (ASTM E648):** 0.45 W/cm² - Class 1
- 2.10. **Smoke Development (ASTM E662):** < 450

3. INSTALLATION

Adhesives: No adhesive required

See Aloft Luxury Vinyl Plank Click installation instructions for complete details.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 7 year light commercial warranty (foot traffic only). See Tarkett limited warranty for details.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Aloft Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



Technical Services Department
 30000 Aurora Road, Solon, Ohio
 44139
 (800) 899-8916 ext 9297
 Fax (440) 632-5643
 email: info@johnsonite.com



THE ULTIMATE
FLOORING EXPERIENCE