MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 926 Resilient Flooring Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

SECTION 1. PRODUCT IDENTIFICATION

PRODUCT NAME: JOHNSONITE 926 CHEMICAL FAMILY: Adhesive Compound

SECTION 2. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

CAS Number Chemical Name % by Weight **ACGIH TLV OSHA PEL**

None required reporting

SECTION 3. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Eyes, skin, inhalation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause slight to moderate irritation, redness, tearing.

SKIN CONTACT: No adverse effects expected with short term, acute exposure. Repeated, extended contact may cause irritation, itching, or reddening.

INGESTION: May cause discomfort, nausea, and diarrhea to digestive tract.

INHALATION: Under normal conditions where product is properly applied no adverse effects are expected. May cause slight respiratory discomfort with extended, excessive exposure to concentrated, unventilated vapors.

CHRONIC: None known.

CARCINOGENICITY: This product contains no ingredient above the OSHA minimum reporting threshold listed as a carcinogen by IARC, NTP, or OSHA

SECTION 4. FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. Contact a physician if irritation occurs.

SKIN CONTACT: Wash with soap and water.

INGESTION: Do not induce vomiting, contact a physician.

INHALATION: Remove to fresh air.

SECTION 5. FIRE-FIGHTING MEASURES

FLASH POINT (o)F: None.

FIRE-FIGHTING INSTRUCTIONS: Use protective clothing and self-contained breathing apparatus.

EXTINGUISHING MEDIA: Water fog, CO2, dry chemical, and chemical foam.

DECOMPOSITION PRODUCTS: Dried combusted material may produce CO, CO2, H2O, NxO, smoke, and

other hydrocarbons.

SECTION 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill. Transfer spill material to secure container(s) for reuse or disposal. Dispense sand, sawdust, or vermiculite and absorb spill residue. Collect and place in waste container. Wash area thoroughly with water.

MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 926 Resilient Flooring Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

SECTION 7. HANDLING AND STORAGE

HANDLING: Use good hygienic practices. (Wash hands before eating, using washroom, or smoking.) Keep out

of the reach of children.

STORAGE: Store above 40o F.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: Wear safety glasses with side shields or splash goggles if contact with material is likely.

SKIN PROTECTION: Wear rubber gloves where contact with material is likely.

RESPIRATORY PROTECTION: Not normally required with good ventilation.

ENGINEERING CONTROLS: Normal room ventilation. Open windows and doors, use floor and ceiling fans to ventilate work area during application.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 212

SPECIFIC GRAVITY (WATER = 1): 1.1 VAPOR PRESSURE: Same as water. VAPOR DENSITY (air=1): Same as water.

% VOLATILE BY WEIGHT: 40

pH: 9.5 - 10

APPEARANCE AND ODOR: Light tan colored creamy paste with slight odor.

SECTION 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.
POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

SECTION 11. TOXICOLOGICAL INFORMATION

No information.

SECTION 12. ECOLOGICAL INFORMATION

No information.

MATERIAL SAFETY DATA SHEET

Supplier: Johnsonite, Inc. Product: 926 Resilient Flooring Adhesive

16910 Munn Road, Chagrin Falls, Ohio 44023

24-Hour Emergency Telephone - Chemtrec: (800-424-9300)

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local regulations.

SECTION 14. TRANSPORT INFORMATION

For domestic transportation purposes, this product is not designated as a hazardous material by the U.S. Department of Transportation.

SECTION 15. REGULATORY INFORMATION

TSCA: All ingredients are listed on the TSCA inventory.

CANADIAN DSL: All ingredients within this product are listed on the Canadian DSL (Domestic Substances List). SARA TITLE III:

Section 311 and 312 Health and Physical Hazards:

ImmediateDelayedFirePressureReactivity[][][]

Section 313 Reportable Chemicals: No components at or above EPA reporting thresholds.

CALIFORNIA PROPOSITION 65: No reportable listed substances.

VOLATILE ORGANIC COMPOUNDS: <0.01% or <0.0009 pounds/gallon.

HAZARDOUS AIR POLLUTANTS: None reportable.

CALIFORNIA VOC (Volatile Organic Compound) COMPLIANCE:

Solvent Free Product.

SCAQMD Rule 1168: VOC compliant.

SCAQMD Rule 443.1: Grams of VOC per Liter of Material < 1 gram/liter.

Grams of VOC per Liter of Coating < 1 gram/liter.

SECTION 16. OTHER INFORMATION

HMIS RATINGS: Health = 1 Flammability = 0

Reactivity = 0 Personal Protective Equipment = B

Hazard rating scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe

Johnsonite believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

DATE ISSUED: January 3, 2012 CONTACT: Don Styka