Azrock VCT

DESCRIPTION

Azrock VCT combines engaging color with an extensive palette giving you the opportunity to create highly styled, durable and economical floor designs with stunning visual impact. With Azrock VCT, whatever you imagine can be created and VCT is ideal for healthcare, education, retail and public spaces.

Technical Data	Standards	VCT	Solids & Feature Strips
Type of Floor Covering		Vinyl Composition Tile	Vinyl Composition Tile
Classification	ASTM F 1066	Class 2 Through Pattern	Class 1 Solid Color
Total Thickness		1/8" (3.2 mm)	1/8" (3.2 mm)
Static Load Limit	ASTM F 970	150 psi	150 psi
Tile Size Weight/sq. ft./m² Carton Quantity Carton Weight		12" x 12" (305 mm x 305 mm) 1.4 lbs sq. ft. (14.0 lbs. m²) 45 tiles = 45 sq. ft. (4.18 m²) 64 lbs (29.0 kg)	12" x 12" (305 mm x 305 mm) 1.4 lbs sq. ft. (14.0 lbs. m²) 45 tiles = 45 sq. ft. (4.18 m²) 64 lbs (29.0 kg)
Flammability	ASTM E 648	Class 1 >0.45 CRF	Class 1 >0.45 CRF
Smoke Density	ASTM E 662	<450	<450
Slip Resistance SCOF	ADA Compliant		
Chemical Resistance		Good	Good
Colors		73 Standard Price	4 Premium Price Solids
Warranty		5 Year LIMITED Warranty. See www.johnsonite.com for complete warranty information.	5 Year LIMITED Warranty. See www.johnsonite.com for complete warranty information.
Maintenance		Conventional VCT Maintenance 3-5+ coats of finish*	Conventional VCT Maintenance 3-5+ coats of finish*

* Depending upon use of the floor.

Please visit johnsonite.com for the most updated specifications, and installation, cleaning and maintenance instructions.

How to Order: V-(XXX) or V-(XXXX) Color Number
VS(XXX) Color Number

Sustainable Facts

Azrock VCT — Possible LEED Credit Contribution

Construction Waste Management — 1-2
ReStart® Reclamation Program
MR 2

Recycled Content — 1-2
Pre-Consumer 10%
Post-Consumer 12%
MR 4

Regional Materials — 1-2
Manufactured in Houston, Texas, an ISO 14001 facility
MR 5

Indoor Air Quality — 1
Low Emitting materials EQ 4.3
FloorScore certified and meets CA 01350
Phthalate free, except for recycled materials
TVOC ≤ 10 µg/m³

SpraySmart

- Immediate Occupancy
- Reduce Install Time
- Environmentally Friendly

This folder is made from 100% recycled materials and printed with soy based ink. Every component of this sample set – from folder to contents – is 100% recyclable. EVERYTHING will be recycled back into future products including Tarkett flooring. **To recycle this sample set place in an envelope or mailer and mail to: Tarkett Recycling Center, 1 Looseleaf Lane, Vincent, AL 35178.**

The Johnsonite system includes transitions and finishing borders (wall base) to complete your flooring design and installation.

www.johnsonite.com

SPEED SWATCH
800-558-2240

16910 Munn Road
Chagrin Falls, OH 44023
800-899-8916 or 440-543-8916

johnsonite.com

Tarkett® | THE ULTIMATE FLOORING EXPERIENCE

©2012 Tarkett
Printed in the USA 1/12

The contents of this document including, but not limited to, all text and images (Content) are owned by Johnsonite Inc. with all rights reserved unless otherwise noted. Any Content that is a trademark, logo, or service mark is also a registered and unregistered trademark of Johnsonite Inc. Your use of any Content without the written permission of Johnsonite Inc. is strictly prohibited.