



ADHESIVES



Tarkett 959

Vinyl Tile and Plank Adhesive

I.D. Inspiration™ Luxury Vinyl Tile



THE ULTIMATE
FLOORING EXPERIENCE

Tarkett959

Tarkett 959 is a solvent-free, installer-friendly adhesive specifically formulated for installing the following Tarkett Residential and Johnsonite LVT, VET, SVT and underlayment products:

- Access
- Color Essence SR™
- FiberFloor®
- Origins
- Aloft™ Glue Down
- Cortina Grande™
- Gemstone™
- PermaStone®
- Azterra™
- Cortina Grande SR™
- I.D. Freedom™
- SureStart™
- Color Essence™
- Crossroads™
- I.D. Inspiration™
- Underlayment
- Vinyl Sheet (Felt Vista®)

It is a versatile luxury and solid vinyl tile and plank adhesive that can be used on all grades of concrete. Tarkett 959 is *Cradle to Cradle Certified™* Gold, the highest level of certification offered for a flooring adhesive. Tarkett 959 also reduces installation time compared to traditional hard-setting adhesives. In addition, it contains a minimum of 20% post-consumer content.

Technical Data	Standards	959 Flooring Adhesive
Adhesive Type		Acrylic
Appearance		White
Odor		Mild Odor
Flash Point		> 212 ° F
NFPA 704 Flammability Rating		0 - <i>Non-flammable</i>
Storage		Store Between 50 ° F & 120 ° F
Shelf Life		2 Years (If unopened)
Open Time		25-40 Minutes
Working Time		2 Hours
VOC Content		< 0.0 g/ml Calculated
Foot Traffic Permitted		Minimum 24 hrs. After Installation
Heavy Rolling Traffic Permitted		Minimum 72 hrs. After Installation
pH Tolerance	ASTM F710	7.0-10.0 pH
Relative Humidity Tolerance	ASTM F2170 ASTM F1869	90% RH 8 lbs. per 1,000 ft.2/24 hrs.
Underfloor Heating Systems		Yes

Please visit www.tarkettna.com for the most updated specifications and installation, cleaning and maintenance instructions.

Sustainability Facts	
To learn more, visit www.tarkettna.com .	
Tarkett 959	LEED Credits Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Material Reuse Supports Reuse & Recycling of Flooring MR 3	1-2
Cradle to Cradle Gold Level - Highest level from C2C for flooring adhesive	1-2
People-Friendly Spaces Low-emitting Materials IEQ 4.1 Adhesives, FloorScore™ Certified & Meets CA 01350	1
SCS Certified Must contain a minimum 20% post-consumer content	



COVERAGE:

All flooring types listed porous & non-porous surfaces

Porous:

1/16" x 1/16" x 1/16" V-notch trowel;
not to exceed 150-175 sq. ft. per gallon

Non-porous:

1/32" x 1/16" x 1/32" U-notch trowel;
not to exceed 250-300 sq. ft. per gallon

