



ADHESIVES

RollSmart™

Fast-Drying Vinyl Flooring Adhesive

iQ™ Granit™ Homogeneous Vinyl Sheet



THE ULTIMATE
FLOORING EXPERIENCE



RollSmart is a solvent-free, easy-to-apply adhesive specifically formulated for installing the following Commercial LVT and Sheet products*:

- Accent®
- Aria™
- iQ™ Granit™ Safe-T
- iQ® Natural
- Accent® Flourish
- I.D. Freedom™
- iQ™ Granit® Micro
- iQ® Optima®
- Accent® Wood Safe-T
- I.D. Inspiration™
- Marbled Safe-T
- Standard Plus
- Aloft™ Glue Down
- iQ™ Granit™
- Melodia®

*Not approved for Acoustiflo® products

This innovative adhesive is applied using a 3/8" nap paint roller and dries quickly to facilitate fast installation times. RollSmart eliminates trowel marks telegraphing and is approved for use under hospital beds.

RollSmart flooring adhesive is an environmentally friendly, non-toxic and non-flammable intelligent adhesive option enabling immediate occupancy; an important benefit for healthcare, education, retail and other environments where foot traffic and rolling traffic are prevalent.

Technical Data	Standards	RollSmart Flooring Adhesive
Adhesive Type		Acrylic
Appearance		Light Blue
Odor		Sweet Mild Odor
Flash Point		> 212 ° F
NFPA 704 Flammability Rating		0 - <i>Non-flammable</i>
Storage		Store Between 50 ° F & 120 ° F
Shelf Life		2 Years (If unopened)
Open Time		10-15 Minutes
Working Time		2 Hours
VOC Content		< 0.0 g/ml Calculated
Foot Traffic Permitted		Immediately After Installation
Heavy Rolling Traffic Permitted		Immediately After Installation
pH Tolerance	ASTM F710	7.0-10.0 pH
Substrate Moisture Tolerance	ASTM F2170 ASTM F1869	90% RH 8 lbs. per 1,000 ft.²/24 hrs.
Underfloor Heating Systems		Yes
Please visit www.tarkettna.com for the most updated specifications and installation, cleaning and maintenance instructions.		

COVERAGE:
All flooring types listed porous & non-porous surfaces

3/8" Nap Paint Roller (w/ a paint tray & a provided wet film thickness gauge); not to exceed 350-400 sq. ft. per gallon

Sustainability Facts	
To learn more, visit www.tarkettna.com .	
RollSmart	LEED Credits Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Material Reuse Supports Reuse & Recycling of Flooring MR 3 1	1-2
Regional Materials Manufactured in Dalton, GA - an ISO 9001 Facility MR 5	1-2
People-Friendly Spaces Low-emitting Materials IEQ 4.1 Adhesives, FloorScore™ Certified & Meets CA 01350	1
Return On Investment Requires Fewer Man Hours to Install Allows immediate post installation occupancy	

RollSmart™	
For Use Under Hospital Beds	✓
Eliminates Trowel Marks	✓
Heat Weld Immediately	✓
Increased Limits for Moisture and pH	✓
Supports Reuse and Recycling of Flooring	✓
Immediate Traffic After Installation, Including Rolling Loads	✓
Cradle to Cradle - Bronze Certification	✓

