

# Cortina Grande® & Karim Kolors

Technical Data	Standards	Cortina Grande
Type of Floor Covering		Solid Vinyl Tile
Classification	ASTM F 1700	Meets Requirements
Total Thickness		1/8" (3.2 mm)
Static Load Limit	ASTM F 970†	800 psi (modified)
Tile Size		16" x 16" (40.6 cm x 40.6 cm)
Weight/sq. ft./m <sup>2</sup>		1.22 lbs sq. ft. (13.08 lbs. m <sup>2</sup> )
Carton Quantity		25 tiles = 44.44 sq. ft. (4.12 m <sup>2</sup> )
Carton Weight		54 lbs (24.5 kg)
Flammability	ASTM E 648	Class 1 > 0.45 CRF
Smoke Density	ASTM E 662	< 450
Slip Resistance SCOF	ASTM D 2047	SCOF ≥ 0.5 - Both smooth and slip resistant (SR)
Chemical Resistance	ASTM F 925	Good
Colors		50 smooth (8 are Karim Kolors), 6 slip resistant
Warranty		10 Year LIMITED Warranty. See tarkettna.com for complete warranty information.
Maintenance		2 coats of finish/Flexible maintenance depending upon use of the floor*

\* Contact Tech Services for flexible maintenance options.

† Static load limit per ASTM 970 modified by specifying a higher load.

Please visit tarkettna.com for the most updated specifications, and installation, cleaning and maintenance instructions.

The Johnsonite system includes transitions and finishing borders (wall base) to complete your flooring design and installation.

**How to Order:** Smooth: CG(XXX) Color Number Slip Resistant: CG(XXX) Color Number SR



**SPEED SWITCH**  
800-899-8916

16910 Munn Road  
Chagrin Falls, OH 44023  
800-899-8916 or 440-543-8916



THE ULTIMATE  
FLOORING EXPERIENCE

tarkettna.com

©2014 Tarkett  
Printed in the USA 6/14

The contents of this document including, but not limited to, all text and images (Content) are owned by Johnsonite Inc. with all rights reserved unless otherwise noted. Any Content that is a trademark, logo, or service mark is also a registered and unregistered trademark of Johnsonite Inc. Your use of any Content without the written permission of Johnsonite Inc. is strictly prohibited.